

A black Axicon 6525-S barcode verifier is shown from a three-quarter perspective. It is a handheld device with a trigger on the side and a cable extending from the back. A barcode is partially visible on the surface it is resting on. The device has a red label on top with the Axicon logo and model number.**axicon**

THE BARCODE EXPERTS

Features

100 verification scans
per second

ISO/IEC compliant
verification

Lightweight and
portable

Automatic variable
aperture

User configurable

Axicon 6525-S

High speed barcode verifier

The Axicon 6525-S barcode verifier is designed to verify linear barcodes with a maximum width, including quiet zones, of 125 mm. This means only one verifier is needed to check all your GS1 barcodes - EAN/UPC, ITF-14 and GS1-128 - if the outer case and logistics label barcodes are not at their maximum size. For anyone printing barcode labels using a 100mm (4 inch) wide printhead, this verifier is perfect. It can also be used to check Code 39, Code 128, HIBC, CIP, PZN and other codes.

Features

The 'S' range of Axicon verifiers has a continuous scan feature, which means that obtaining at least ten different readings throughout the height of the barcode (as required by ISO/IEC) is much faster. Simply place the verifier slightly above or below the barcode, press the trigger and slide the verifier over the code - in less than a second you can have results of up to 100 scans of the code at different points in the bar height.

Software

Designed to function with any PC running any currently supported version of Microsoft Windows. The software is always updated to meet latest requirements of the GS1 General Specifications, and is available free of charge from our website.

About Axicon

Axicon Auto ID is a world leader in barcode verification, having developed and manufactured our own range of verifiers since 1989. Axicon barcode verifiers are used to measure the quality of linear and matrix barcodes, on all levels of product packaging.



Church Road, Weston on the Green, Oxfordshire, OX25 3QP, UK
Tel: +44 (0)1869 351155 | Email: sales@axicon.com
Web: www.axicon.com



Software specifications



Symbologies verified	EAN-8, EAN-13 and UPC-A (with or without add-ons), UPC-E, GS1 DataBar (all symbols), ITF-14, GS1-128, Code 39, Code 93, Code 128, Codabar, ITF, MSI Plessey, (all symbols no wider than 125 mm)
Application standards	AIAG, Belgian Pharmacodes (MSI and Unique), CIP39, Coupon Codes (UK, USA, Euro), GS1 Application Identifier Check, HIBC, ISBN/ISSN, Italian Pharmacode (IMH), LPPR, M&S, PZN, SISAC, Variable Measure Codes (Branded, Instore, Australian).
Analysis	All ISO/IEC parameters, ANSI option, decodability per symbol character, nominal x-dimension, average bar gain, check digit validation, print contrast measurement (PCS), wide-to-narrow ratio, symbol structure, quiet zones.
Calibration logging	Record of date and time for ISO 9001 records
Configurable options	Simplified pass/fail display, number of scans per verification, pass grade, print and file save options, audible warnings, calibration reminder, check digit validation, report generation tool, GTIN validation (with appropriate database). CSV file saving, user data, data checking for various applications

Hardware specifications

Dimensions	145 x 113 x 128 mm (5.7" x 4.4" x 5.0")
IP Options	Also available with IP50 (60529) rated protection.
Weight	675 g (23.8 oz)
Construction	Aluminium, CCD sensor, LED illumination
Interface and power consumption	USB 2.0 150mA at 5v.
Aperture reference numbers	05, 06, 10, and 20
Wavelength of light	660 nm
Maximum scan width	125 mm (4.9")

General information

Regulatory approvals	CE marking (compliant with RoHS and EMC directives) Compliant with ISO/IEC 15416 and ISO/IEC 15426-1 Can meet the requirements of 21 CFR part 11.
Operating range	Operating temperature: 10° to 40°C Storage temperature: -20° to 70°C Relative humidity: 25% to 80% @ 40°C non-condensing.
Warranty	Two years parts and labour - return to bench.



All trademarks are acknowledged as belonging to their respective companies.
As Axicon continually improves its products, the specifications and features explained here are subject to change without notice.

